## WHAT IS CLAIMED IS:

 A toner supply container detachably mountable to an image forming apparatus, comprising:

a main body, provided with an opening for permitting discharge of the toner, for accommodating the toner;

SON Y

ļ.

ļ±

IJ

U

C) L4

TU TU 5

10

a sealing member for unsealably sealing the opening;

wherein the opening is unsealed by tearing a part of said sealing member;

wherein a pattern of welding with which said sealing member is welded on the main body of the container is inclined inwardly with respect to a tearing direction at a laterally outward end portion at a tearing starting side end portion.

A toner supply container according to Claim
 wherein the welding pattern is inclined
 rectilinearly.

20

15

- 3. A toner supply container according to Claim

  1. wherein said welding pattern is inclined with

  curvature.
- A) 25

  1. Wherein the welding pattern is cut-away toward downstream with respect to the tearing direction, at a portion where the tearing starts in a welded portion.

34

A toner supply container according to Claim 5. 1, wherein said sealing member has a seal portion welded to the main body of said container, and a sealing member pulling portion extended and folded back therefrom.

ϱ

١D

TU:

A toner supply container according to Claim 1, wherein said sealing member is provided with a tearing guide portion provided by laser irradiation.

10

A toner supply container according to Claim 1, wherein said sealing member has a cover film sealing the opening and a tear tape for tearing the cover film.

15

A process cartridge detachably mountable to an image forming apparatus, comprising:

a developing portion, having a photosensitive member, for developing a latent image on the photosensitive member;

a toner accommodating portion for accommodating toner to said developing portion, said toner accommodating portion is provided with an opening for permitting discharging of the toner;

25

20

a sealing member for unsealably sealing the opening, wherein said sealing member has a seal portion welded to the main body of said container, and sub Aa cont. a sealing member pulling portion extended and folded back therefrom.

wherein the opening is unsealed by tearing a part of said sealing member,

wherein wherein a pattern of welding with which said sealing member is welded on the main body of the container is inclined inwardly with respect to a tearing direction at a laterally outward end portion at a tearing starting side end portion.

10

25

5

- 9. A toner supply container according to Claim 8. wherein the welding pattern is inclined rectilinearly.
- 10. A toner supply container according to Claim
  8, wherein said welding pattern is inclined with
  curvature.
- 11. A toner supply container according to Claim
  20 8, wherein the welding pattern is cut-away toward
  downstream with respect to the tearing direction, at a
  portion where the tearing starts in a welded portion.
  - 12. A toner supply container according to Claim 8, wherein said sealing member is provided with a tearing guide portion provided by laser irradiation.

enp cone.

A toner supply container according to Claim 13. 8, wherein said sealing member has a cover film sealing the opening and a tear tape for tearing the eover film.

5

10

15 Hard with than their their their

20

25